



RETRATTILE 54

Immersion type shrinking tank

- Immersion type shrinking tank for a total and uniform adhesion of the packaging to the vacuum packed product and for an outstanding display.
- N.B. Shrinking with special vacuum thermo-shrinking bags only.
- Built in stainless steel
- Working cycle 2,2 seconds
- Electronic thermostat for water temperature control (+ 80 °C ÷ + 94 °C)
- Tank capacity 54 litres approx. (max. immersion height 250 mm)
- Working plane 430x400 mm
- Immersion heating elements
- Direct water loading into the tank
- Water unloading with rear manual security tap
- Filling bodies (separation barriers liquids/air) to reduce evaporation
- Tank closing cover



Optional

- Hood with operation control on the machine's panel
- Electronically variable speed of the working cycle (from 1 up to 3,5 seconds)

Technical Information

Model	Width	Depth	Height	Tank Dimensions	Tank Capacity	Voltage	Power
	L mm	P mm	H mm	mm	m ³ /h	V~	W
Retrattile 54	620	670	880	450x430x415H	54	3N	10.3
Retrattile 54V With variable speed	620	670	880	450x430x415H	54	3N	10.3



13 Stilebrook Road, Olney, Buckinghamshire MK46 5EA
Tel. 01908 565758

Reg. No. 3554721 Vat Regn. No. 716 2881 27